



# Arctic Manufacturing Ltd.

3323 Hart Highway, Prince George, B.C. V2K 1M8

ph: (250) 962-9631

fx: (250) 962-7500

[www.arcticmfg.com](http://www.arcticmfg.com)

TA-26.1L-LL 196" w/b Short Logger



**Chassis:** Heavy Duty QT-100 frame, QT-100 cross members. "Huck" bolt fasteners for cross-member locations.

**Suspension:** Arctic Mfg Ltd walking beam suspension with 2-piece end caps. Urethane bushings for all pivot/mount locations and 3 1/2" trunnion shaft on rear suspension. Rubber Quad-Block front suspension reduces spring bounce.

**Axle:** Dana D22FC-77" track, 5/8" wall with weld-on spiders

**Hubs:** 10-Stud cast hub pilot hubs, with long studs for dual aluminum wheels.

**Drums:** 10 stud cast out-board type 16 1/2" x 7" brake drums.

- Brakes:** CM29 "Q-Type" (23,000lb OEM certifiable G.A.W.R.), enclosed air-ride camshafts with HD snap-rings, Haldex automatic slack adjusters. #30/30 spring brakes Haldex 4S/2M Anti-Lock Brake System.
- Tires:** Michelin XXY-3 11R24.5 load-range (H).
- Rims:** Alcoa aluminum machine finished 8.25 x 24.5 rims.
- Bunks:** 8'-6" LW-U Bunks.
- Reach:** Single Stage A-Frame Reach with Urethane Bushed Swivel Eye.
- Scales:** Vulcan V320 VSL Side-Mount Short Logger Electronic's.
- Air:** "SX" maxi brake air system with anti-compounding full function valves with a "Hostler" Quick release valve
- Electrical:** C.M.V.S.S. compliance lighting system. Sealed shock resistant lexan tail and clearance/marker lights. Sealed Bobtail receptacles and plugs for all exposed electrical harness. LED tail and marker lights.
- Paint:** DuPont Anti-corrosive zinc high-build epoxy primer with DuPont Imron epoxy single stage two part, same color on frame, axle, hubs. Color: Black. C.M.V.S.S. compliance reflective tape. Media blasted prior to priming/painting.
- Rating:** 41,731 kg G.V.W.R.
- Options:** Light-Weight Hub and Bi-Metal Drums.  
Steel Wheel as well as Polished Aluminum Wheels.  
11R22.5 XZY-3 (H) tires.  
S.I. scales and electronics.

